



M12 x 1 round connector female connector M12 x 1 WAK5-2/P00



- robust and pre-assembled round connector
- plastic moulding
- Degree of protection IP67
- also available with different cable lengths and of different materials
- PVC cable
- suited to average mechanical stress

Wiring diagram



cable quality P00

Pure PVC cable, resistant to average mechanical strain, for use in packaging machinery as well as assembly and production lines. Good resistance against acids and alkalis and thus suited for use in the food and beverage industry. Limited resistance to abrasion, conditional resistance to oils and chemicals.

Type	WAK5-2/P00
Ident-No.	8007067
Connector	female connector, M12 x 1, straight
Polarity	4-pole + PE
Contacts	metal, CuZn, gold-plated
Contact carriers	plastic, TPU, black also with B type coding on request
Grip	plastic, TPU, blue stainless steel coupling nut/screw available on request
Seal	plastic, FPM/FKM
Degree of protection	IP67, only with screws tightened
Mechanical lifespan	min. 100 Contact durability
Pollution degree	3/2
	also with B type coding on request stainless steel coupling nut/screw available on request
Cable	P00, LiYY
Cable diameter	Ø 5.5 mm
Cable length	2 m
Cable jacket	PVC, grey
Core insulation material	PVC
Core insulation colours	BN, WH, BU, BK, GNYE
Core cross-section	4 x 0.34 mm ²
Core cross-section PE	1 x 0.5 mm ²
Litz wire arrangement	19 x 0.15 mm
Litz wire design PE	16 x 0.2 mm
Bending radius (moving state)	minimum 10 x Cable diameter
Rated voltage	max. 60 V
Insulation resistance	≥ 10 ⁹ Ω
Ampacity	4 A
Forward resistance	≤ 5 mΩ
Ambient temperature Connector	-30 ... + 90 °C
Cable ambient temperature	-40 ... + 80 °C