



Main

Range of product	GV2 GV3
Product or component type	Auxiliary contact block
Product compatibility	GV2L GV2LE GV2ME GV2P GV3L GV3P LS1D32
Auxiliary contacts operation	Instantaneous
Pole contact composition	2 NO
Connections - terminals	Screw clamps terminals control circuit 2 0.75...2.5 mm ² flexible without Screw clamps terminals control circuit 1 0.75...1.5 mm ² flexible with Screw clamps terminals control circuit 2 1...2.5 mm ² solid Screw clamps terminals control circuit 1 0.75...2.5 mm ² flexible without Screw clamps terminals control circuit 1 1...2.5 mm ² solid
Quantity per set	Set of 10

Complementary

Mounting location	Front side
[Ui] rated insulation voltage	250 V IEC 60947-1 control circuit 300 V CSA C22-2 No 14 control circuit 300 V UL 508 control circuit
[Ue] rated operational voltage	24 V DC control circuit 24 V AC control circuit 48 V DC control circuit 48 V AC control circuit 60 V DC control circuit 110...127 V AC control circuit 230...240 V AC control circuit
[Ith] conventional free air thermal current	1 A CSA C22-2 No 14 control circuit 1 A UL 508 control circuit 2.5 A IEC 60947-5-1 control circuit
Protection type	GB2CB06 circuit breaker ≤ 10 A control circuit GG fuse ≤ 10 A control circuit
Mechanical durability	100000 cycles
Minimum switching current	5 mA control circuit
Minimum switching voltage	17 V control circuit
Rated operational power in VA	48 VA 24 V AC-15 100000 cycles control circuit 60 VA 48 V AC-15 100000 cycles control circuit 120 VA 110...120 V AC-15 100000 cycles control circuit 120 VA 230...240 V AC-15 100000 cycles control circuit
Rated operational power in W	9 W 60 V DC-13 100000 cycles control circuit 15 W 48 V DC-13 100000 cycles control circuit 24 W 24 V DC-13 100000 cycles control circuit
Tightening torque	≤ 1.4 N.m control circuit screw-clamp terminals
Height	10 mm
Width	44.5 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Depth	15 mm
Product weight	0.02 kg

Environment

RoHS EUR conformity date	0701
RoHS EUR status	Compliant