

## XUB0BNSWL2

photo-electric sensor - XUB - multi - 90° - Sn  
0..18m - 12..24VDC - cable 2m



### Main

Range of product	OsiSense XU
Series name	Universal
Specific application of photoelectric detector	Object
Sensor name	XUB
Sensor design	M18
Material	Metal
Detection system	Diffuse Diffuse with background suppression Polarised reflex Thru beam
Emission	Infrared diffuse Infrared diffuse with background suppression Infrared thru beam Red polarised reflex
Line of sight type	90° lateral
[Sn] nominal sensing distance	0.11 m diffuse with background suppression 0.2 m diffuse 1.5 m polarised reflex 10 m thru beam
Wiring technique	3 wires
Type of output signal	Discrete
Discrete output function	1 NO or 1 NC programmable
Discrete output type	NPN
Add on output	Without
Electrical connection	Cable
Cable length	2 m
Wire insulation material	PvR
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Switching capacity in mA	≤ 100 mA , overload and short-circuit protection
Diameter	18 mm

### Complementary

Electronic sensor type	Photo-electric sensor
Enclosure material	Nickel plated brass
Lens material	PMMA
Maximum sensing distance	0.11 m diffuse with background suppression 0.3 m diffuse 2 m polarised reflex 14 m thru beam
Output type	Solid state
Status LED	1 LED (yellow) for output state 1 LED (green) for supply 1 LED (red) for instability
Supply circuit type	DC
Supply voltage limits	10...36 V DC
Switching frequency	≤ 250 Hz
Voltage drop	1.5 V (closed state)
Current consumption	35 mA at no-load
Delay first up	< 200 ms

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Delay response	< 2 ms
Delay recovery	< 2 ms
Setting-up	Self-teaching
Length	78 mm
Product weight	0.11 kg

## Environment

Product certifications	CE CSA UL
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...70 °C
Vibration resistance	7 gn , amplitude +/- 1.5 mm (f = 10...55 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn , duration 11 ms conforming to IEC 60068-2-27
IP degree of protection	IP65 double insulation conforming to IEC 60529 IP67 double insulation conforming to IEC 60529
RoHS EUR conformity date	0847
RoHS EUR status	Compliant