


# XPER929

single foot switch - IP66 - without cover -  
metallic - orange - 2 NC + 2 NO



## Main

Range of product	Harmony XPE
Product or component type	Foot switch
Material	Metal
Foot switch type	Single foot switch
Device short name	XPER
Protective cover	Without
Trigger mechanism	With trigger mechanism
Contacts operation	Analog output
Contacts type and composition	2 NC + NO
Colour	Orange

## Complementary

Positive opening	With conforming to EN/IEC 60947-5-1 appendix K
[Us] rated supply voltage	24...48 V DC
Supply voltage limits	19...58 V
Current consumption	4 mA no load
Output current drift	-12...2 % at -25...70 °C -6...2 % at 0...50 °C
Connections - terminals	Screw clamp terminal : ≤ 1 x 2.5 mm <sup>2</sup> with or without cable end Screw clamp terminal : ≤ 2 x 1.5 mm <sup>2</sup> with or without cable end
Cable entry	2 entries tapped for Pg 16 cable gland
Mechanical durability	15000000 cycles
[Ie] rated operational current	0.27 A , 250 V , DC-13 , Q300 conforming to EN/IEC 60947-5-1 appendix A 3 A , 240 V , AC-15 , A300
[Ui] rated insulation voltage	300 V conforming to UL 508 300 V conforming to CSA C22-2 No 14 500 V , degree of pollution: 3 conforming to EN/IEC 60947-1 500 V , degree of pollution: 3 conforming to NF C 20-040 group C 500 V , degree of pollution: 3 conforming to VDE 0110 group C
[Uimp] rated impulse withstand voltage	6 kV conforming to EN/IEC 60947-1
Resistance across terminals	≤ 25 mOhm conforming to IEC 60255-7 category 3 ≤ 25 mOhm conforming to NF C 93-050 method A
Short circuit protection	10 A cartridge fuse type gG conforming to VDE 0660-200 10 A cartridge fuse type gG conforming to EN/IEC 60947-5-1
Operational power in W	4 W DC-13 , operating rate: 60 cyc/mn ,5000000 cycles ,120 V , load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C 7 W DC-13 , operating rate: 60 cyc/mn ,5000000 cycles ,48 V , load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C 10 W DC-13 , operating rate: 60 cyc/mn ,5000000 cycles ,24 V , load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C
Product weight	1.22 kg

## Environment

Standards	EN/IEC 60947-5-1 VDE 0660-200
Product certifications	CSA FI
Protective treatment	TC
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C

Vibration resistance	15 gn (f = 10...500 Hz) conforming to IEC 60068-2-6
Shock resistance	20 gn conforming to IEC 60068-2-27 150 gn conforming to NF E 09-031
Class of protection against electric shock	Class I conforming to NF C 20-030 Class I conforming to EN/IEC 61140
IP degree of protection	IP66 conforming to IEC 60529
RoHS EUR conformity date	0852
RoHS EUR status	Compliant